

for solid-fuel heating systems

**ebm-papst Mulfingen GmbH & Co. KG**

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

**Nominal data**

|                             |                    |         |
|-----------------------------|--------------------|---------|
| Type                        | R2E150-AN89-11     |         |
| Motor                       | M2E068-BF          |         |
| Phase                       |                    | 1~      |
| Nominal voltage             | VAC                | 115     |
| Frequency                   | Hz                 | 60      |
| Method of obtaining data    |                    | fa      |
| Valid for approval/standard |                    | UL 2111 |
| Power consumption           | W                  | 40      |
| Capacitor                   | µF                 | 3       |
| Capacitor voltage           | VDB                | 220     |
| Capacitor standard          |                    | UL      |
| Min. back pressure          | Pa                 | 0       |
| Min. back pressure          | inH <sub>2</sub> O | 0       |
| Min. ambient temperature    | °C                 | -25     |
| Max. ambient temperature    | °C                 | 80      |


ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change



## Technical description


|                                                                            |                                                       |
|----------------------------------------------------------------------------|-------------------------------------------------------|
| Weight                                                                     | 1.7 kg                                                |
| Fan size                                                                   | 150 mm                                                |
| Rotor surface                                                              | Unpainted                                             |
| Impeller material                                                          | Sheet steel, stainless                                |
| Number of blades                                                           | 6                                                     |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                 |
| Degree of protection                                                       | IP44; installation- and position-dependent            |
| Insulation class                                                           | "B"                                                   |
| Moisture (F) / Environmental (H) protection class                          | H0 - dry environment                                  |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                               |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                               |
| Installation position                                                      | Any                                                   |
| Mode                                                                       | S1                                                    |
| Motor bearing                                                              | Ball bearing                                          |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                             |
| Motor protection                                                           | Thermal overload protector (TOP) internally connected |
| With cable                                                                 | Variable                                              |
| Protection class                                                           | I (with customer connection of protective earth)      |
| Motor capacitor according to EN 60252-1 in safety protection class         | S2                                                    |
| Conformity with standards                                                  | EN 60335-1; CE                                        |
| Approval                                                                   | CSA C22.2 No. 77; UL 2111                             |

## Product drawing



|     |                                                                                                              |
|-----|--------------------------------------------------------------------------------------------------------------|
| 1   | Cable AWG20; 1x ring terminal, 1x flat push-on receptacle 160389-3 and 2x flat push-on receptacle 3-160256-1 |
| 2   | AMP connector housing 350766-4 with 3x plug pin 926885-1                                                     |
| 2.1 | + (red)                                                                                                      |
| 2.2 | 0 V (black)                                                                                                  |
| 2.3 | out (white)                                                                                                  |


Connection diagram



|     |                        |
|-----|------------------------|
| 1   | Fan connection diagram |
| U1  | blue                   |
| Z   | brown                  |
| U2  | black                  |
| PE  | green/yellow           |
| 2   | Hall IC circuit        |
| 2.1 | Hall IC                |
| 2.2 | red (+5 V)             |
| 2.3 | white (out)            |
| 2.4 | black (0 V)            |



## Curves: Air performance 60 Hz



Measurement: LU-13862-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub> | p <sub>ts</sub> | q <sub>v</sub> | p <sub>ts</sub> |
|---|-----|----|-------------------|----------------|------|----------------|-----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h           | Pa              | cfm            | inH2O           |
| 1 | 115 | 60 | 2550              | 33             | 0.30 | 145            | 0               | 85             | 0.00            |
| 2 | 115 | 60 | 2635              | 32             | 0.28 | 115            | 100             | 65             | 0.40            |
| 3 | 115 | 60 | 2755              | 31             | 0.27 | 75             | 200             | 45             | 0.80            |
| 4 | 115 | 60 | 2865              | 30             | 0.26 | 45             | 280             | 25             | 1.12            |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>ts</sub> = Pressure increase

